

GE/RT8000/HB10

Rule Book

Handbook 10

Handbook 10

Duties of the COSS or SWL and person in charge when using a hand trolley

**Issue 3
September 2014
Comes into force
06 December 2014**



Published by:
RSSB
Block 2 Angel Square
1 Torrens Street
London EC1V 1NY

**Contents approved by Traffic Operation
and Management Standards Committee.**

**For information regarding this document,
contact:**

enquirydesk@rssb.co.uk

**First issued December 2010
Issue 3, September 2014
Comes into force 06 December 2014**

**© Copyright 2014
Rail Safety and Standards Board**

Page

1	General	2
2	Duties of the COSS or SWL	2
3	Duties of the person in charge of the trolley	4

1 General

Unless it says otherwise in company instructions, the instructions in this handbook apply when using hand-controlled trolleys and other manually propelled equipment mounted on rail wheels or runners. All these items are referred to as trolleys in this handbook.

A competent person must always be appointed to be in charge of the trolley while it is in use.

A COSS or SWL must make sure the line is blocked before the trolley is placed on the line. The COSS or SWL can be the person in charge of the trolley.

Each trolley must be fitted with an operational fail-safe braking system. The correct brake handle must be used when operating the trolley.

A trolley must not pass over an axle counter head unless reset arrangements have been agreed.

2 Duties of the COSS or SWL

2.1 Making sure the line is blocked

If you are the COSS, you must make sure the line is blocked as shown in handbook 8 or 9 and the necessary arrangements for the trolley have been made before you allow the trolley to be placed on the line.

If you are the SWL, you must make sure the line is blocked as shown in handbook 21 and the necessary arrangements for the trolley have been made before you allow the trolley to be placed on the line.

2.2 On a running line not under possession

You must agree with the signaller the position any points must be in. You must not allow the trolley to pass any signal at danger without the signaller's authority.

2.3 On a running line in a possession

If you are a COSS working within a possession, you must agree with the ES or SWL when you can allow the trolley to be placed on the line.

2.4 Within a siding

If working within a siding, you must not allow the trolley to be placed on the line until the necessary protection arrangements have been made.

2.5 Level crossings

You must not allow the trolley to:

- pass over a manned level crossing unless the barriers are lowered or the gates are closed to road traffic and you are sure it is safe to do so
- come within the controls of an ABCL or AOCL
- come within the controls of an AHBC unless it is under local control
- pass over an AHBC unless it is under local control and the attendant displays a green handsignal
- pass over a level crossing which has red and green warning lights unless you have made sure it is safe to do so
- pass over a CCTV, OD or RC crossing without the signaller's authority.

3 Duties of the person in charge of the trolley

The person in charge of the trolley must make sure that:

- the trolley's braking system has been tested and is in good order
- the COSS or SWL has given permission before the trolley is put on the line
- the trolley is not placed on or used on a line which has a gradient greater than 1 in 50, unless specially authorised in local instructions
- the trolley is correctly loaded
- the trolley is not overloaded
- no-one rides on the trolley
- the trolley, or its load, does not foul any other line
- the trolley has at least two people with it when moving and one of them must be in charge of the brake
- a red flag or red light is displayed on the trolley - the flag or light must be visible in both directions
- when not being used, the trolley is placed well clear of the line and if left unattended, the trolley must be secured so it cannot be moved.

**Corporate member of
Plain English Campaign
Committed to clearer
communication**

172

